

SR5600 Wearable Scanner

- **Superior Scanning Performance**

Accurately decodes various complex 1D/2D codes at remarkable speed, reducing lag time.

- **950mAh Removable Battery**

Delivers over 20 hours of runtime at room temperature, eliminating the need for frequent charging and ensuring uninterrupted performance during long shifts.

- **NFC One-Tap Pairing, Instant Connection**

Simplifies the setup process—just tap to connect and start using immediately, saving time and effort.

- **Multiple Wearing Options**

Supports ring, glove, and lanyard modes. Ring and glove fit either hand with trigger buttons for instant scanning, adapting to different user habits and freeing your hands for other tasks.

- **Bluetooth 5.3 for Seamless Connectivity**





















Ensures stable connections with various devices and allows smooth switching between them, enabling greater flexibility at work.

- **Rugged Industrial-Grade Protection**

IP65-rated dust and water resistance combined with 1.8-meter drop protection ensures reliable performance even in demanding work conditions.



SR5600 Wearable Scanner Specifications

 Image Sensor 1280 × 1080 CMOS 60 fps	 Illumination White LED	 Aimer Red Cross Laser 650 nm	 Field of View Horizontal 38° Vertical 33°	 Scan Angle Rotation 360° Tilt ±65° Skew ±65°
 Minimum Resolution ≥ 3 mil	 Print Contrast Minimum 20% Reflectance Difference	 Reading Feedback Vibration, Buzzer, LED Indicator	 Symbology Reading Supports all common 1D and 2D barcodes	 Weight 75 g
 Dimensions 63 × 33 × 19.5 mm	 Indication Modes Buzzer LED Indicator Vibration	 Power Source 950 mAh Removable Battery	 Wireless Bluetooth 5.3 range up to 80 m	 Pairing NFC Quick Pairing
 Operating Temperature -20 °C to 50 °C	 Humidity 5%–95% RH (non-condensing)	 Storage Temperature -30 °C to 70 °C	 ESD Protection ±15 kV Air Discharge ±8 kV Direct Discharge	 Protection Rating IP65 1.8 m Drop Resistance

UROVO PTE. LIMITED

Website: en.urovo.com
 Email: urovo@urovo.com
 Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1,
 Singapore 048616

Urovo Europe

Website: europe.urovo.com
 Email: sales-europe@urovo-emea.com
 Address: de Maas 9, 5684PL, Best, the Netherlands

Urovo North America

Website: us.urovo.com
 Email: urovo@urovo.com
 Address: 1990 Main Street, Suite 750, Sarasota,
 Florida 34236

*This page is subject to change
 without prior notice